

Representations of Time Coordinates in FITS

Time and Relative Dimension in Space (V0.90)

Arnold H. Rots,¹ Peter S. Bunclark,^{2,*} Mark R. Calabretta,³ Steven L. Allen,⁴ Richard N. Manchester,³ and William T. Thompson⁵

¹ Harvard-Smithsonian Center for Astrophysics/Smithsonian Astrophysical Observatory, 60 Garden Street MS 67, Cambridge, MA 02138, USA

² Institute of Astronomy, Madingley Road, Cambridge CB3 0HA, UK

³ Australia Telescope National Facility, PO Box 76, Epping, NSW 1710, Australia

⁴ UCO/Lick Observatory, University of California, Santa Cruz, CA 95064, USA

⁵ Adnet Systems, Inc., NASA Goddard Space Flight Center, Code 671, Greenbelt, MD 20771, USA

Received December 25, 2008; accepted January 1, 2009

ABSTRACT

Context. In a series of four previous papers, formulation and specifics of the representation of World Coordinate Transformations in FITS data have been presented. This fifth paper deals with encoding time.

Aims. Time on all scales and precision known in astronomical datasets shall be described by extending the established FITS standard.

Methods. Employing the well-established World Coordinate System framework, and maintaining compatibility with the FITS conventions that are currently in use to specify time, the standard is extended to rigorously describe the time coordinate.

Results. World coordinate functions are defined for temporal axes sampled linearly and as specified by a lookup table.

Key words. methods: data analysis – techniques: image processing

1. Introduction

Time as a dimension in astronomical data presents challenges in its representation in FITS files as great as those met by the previous papers in this series. The first, Paper I (Greisen & Calabretta 2002), lays the groundwork by developing general constructs and related FITS header keywords and the rules for their usage in recording coordinate information. Paper II (Calabretta & Greisen 2002) addresses the specific problem of describing celestial coordinates in a two-dimensional projection of the sky. In Paper III, Greisen et al. (2006) apply these methods to spectral coordinates. Paper IV (Calabretta et al. 2012) extends the formalism to deal with general distortions of the coordinate grid.

This paper, Paper V in the series, formulates the representation of the time axis, or possible multiple time axes, into the FITS World Coordinate System (WCS) previously described. We show how much of the basic structure is employed, while developing extensions to cope with the differences between time and other dimensions; notable amongst these differences is the huge dynamic range covering the highest resolution relative timing to the age of the Universe.

The precision with which any time stamp conforms to any conventional time scale is highly dependent on the characteristics of the acquiring system. The definitions of many conventional time scales vary over their history along with the precision which can be attributed to any time stamp. The meaning of any

time stamp may be ambiguous if a time scale is used for dates prior to its definition by a recognized authority, or for dates after that definition is abandoned. However, common sense should prevail and it would be overly pedantic to require a precision in the description of the time coordinate that far exceeds the accuracy of the temporal information in the data.

In the following sections we will first define the terms of reference of this standard. The next section provides an explanation of the components that are involved and defines the keywords to be used for specifying those components. A section on usage context that includes four header examples refers back to the terms of reference. Finally, we present some concluding remarks.

Generally helpful references may be found in Seidelmann (1992) and McCarthy & Seidelmann (2009).

2. Terms of Reference

Time WCS information needs to be supported in five contexts:

- Recording time stamps in header keywords
- Time coordinate axes in images
- Time columns in tables
- Time coordinate axes in table vector columns
- Time in random groups

We shall distinguish the following components in the specification of time:

* Deceased

- Time Coordinate Frame, containing:
 - Time Scale
 - Time Reference Position
 - Reference Time (the zero point for relative times)
 - Time Reference Direction (if applicable)
 - Planetary and Solar System ephemeris used (if applicable)
- Time Unit
- Corrections, errors, etc.:
 - Time offsets
 - Absolute error
 - Relative error
 - Time resolution
- Durations

The following use cases illustrate the scope of the requirements for time axes.

- Photon arrival times (“event lists”)
- Time-sampled data streams (referred to as “light curves” in some of our communities)
- Pulsar pulse profiles (folded or stacked light curves)
- Image cubes: typically a series of two-dimensional images acquired at regular time spacing, and stacked so the third axis is time. Usually precision isn’t demanding, but the time axis must be integrated into a three-dimensional WCS.
- Simulation data

“Mixed” axes, where spatial or spectral coordinates change as a function of time (e.g., during an observation) represent a special challenge.

Where possible, we have adopted the same keywords as in the OGIP convention¹, which has become a *de facto* standard for representing timing information within high-energy astrophysics data files, particularly from NASA as well as many ESA missions.

Contrary to the convention followed in previous FITS standards papers, Appendix A is to be considered part of this standard. The more subtle issues associated with the definition of time scales are, of necessity, germane to the details of the standard, but it seemed unwieldy to include them in the main text of this paper.

3. Time Values and Representations of Time

Even though we may tend to think of certain representations of time as absolute (ISO-8601, Julian dates), time values in this paper will all be considered relative: elapsed time since a particular reference point in time; it may help to view the “absolute” values as merely relative to a globally accepted zero point. Besselian and Julian epochs are the only exceptions. In the following we will first treat the ISO-8601 representation, then floating point values of elapsed time since a reference value. Concerning the latter, usage cases show that values of time elapsed since a particular reference time cannot always be represented satisfactorily by existing FITS data types. In addition to the 32-bit (E) and 64-bit (D) floating point types it is desirable to have a 128-bit floating point data type. We conclude the section with a specification of epochs.

¹ This convention was developed by the Office of Guest Investigator Programs within the HEASARC (High Energy Astrophysics Science Archive Research Center) at the NASA Goddard Space Flight Center.

3.1. ISO-8601 Datetime Strings

FITS uses a subset of ISO-8601 (which in itself does not imply a particular time scale) for several time-related keywords (Bunclark & Rots 1997), such as DATE-xxx and MJD-xxx. In this paper we will use *datetime* as a pseudo data type. At the present time its values can be written as a character string in A format, but it would be desirable to have it included as a data type in its own right into the FITS standard as type ‘T’. It is premature to prescribe a full format specifier, but we expect it to be similar to the way the A format is handled. If and when an ISO-8601 data type is adopted we will assume that it will be used, rather than the string type.

The full specification for the format of the *datetime* string till now has been:

```
CCYY-MM-DD[Thh:mm:ss[.s...]]
```

All of the time part may be omitted (just leaving the date) or the decimal seconds may be omitted. Leading zeroes may not be omitted and timezone designators are not allowed.

This paper extends the definition to allow five-digit years with a (mandatory) sign. I.e., one may either use the *unsigned* four-digit year format or the *signed* five-digit year format:

```
[±C]CCYY-MM-DD[Thh:mm:ss[.s...]]
```

Note the following:

- The earliest date that may be represented in the four-digit year format is 0000-01-01T00:00:00 (in the year 1 BCE); the latest date is 9999-12-31T23:59:59. This representation of time is tied to the Gregorian calendar (Pope Gregorius 1582) which means that its use for times before 1582 is not defined by the ISO standard itself. However, for use in FITS files we specify that such dates are to be interpreted according to the proleptic application of the rules of Gregorius (1582). For dates not covered by the range we recommend the use of Modified Julian Date (MJD) or Julian Date (JD) numbers or the use of the signed five-digit year format.
- In the five-digit year format the earliest and latest dates are –99999-01-01T00:00:00 (i.e., -100000 BCE) and +99999-12-31T23:59:59.
- In time scale UTC the integer part of the seconds field runs from 00 to 60; in all other time scales the range is 00 to 59.
- This data type is not allowed in image axis descriptions since CRVAL is required to be a floating point value.
- ISO-8601 *datetime* does not imply the use of any particular time scale (see Section 4.2.1).
- As specified by Bunclark & Rots (1997), time zones are explicitly not supported in FITS and, consequently, appending the letter ‘Z’ to a FITS ISO-8601 string is not allowed. The rationale for this rule is that its role in the ISO standard is that of a time zone indicator, not a time scale indicator. As the concept of a time zone is not supported in FITS, the use of time zone indicator is inappropriate.

3.2. Single or Double Precision Floating Point Relative Time

These are existing data types that do not need any particular provisions and can be used when their precision suffices. The following sections deal with situations where double precision floating point does not provide enough precision.

3.3. Higher Precision in Header Keywords

In headers, the value may be written to as many significant figures as required. Such free-format floating point is already recognized in the FITS standard (IAU FITS Working Group, 2008). We emphasize that it always is, and always has been, the implementer’s responsibility to check on the required accuracy of keyword values, rather than to assume that “a double is good enough” (see Section 4.2.4 of the standard), although FITS readers and general applications may need to be checked whether they handle this correctly. Nevertheless, the conclusion is that there are no problems with keyword values as well as the time axis in images.

Note that this technique can also be used in ASCII tables with the use of the F, E, and D formats.

3.4. Higher Precision in Binary Tables: Doublet Vectors

In binary tables one may use pairs of doubles. The time column in such a table shall contain a vector of two doubles where the first component of the doublet contains the integer portion of the time value and the second one the fractional part. We readily admit that a combination of an integer and a floating point number would be preferable, but the use of two doubles allows us to keep the time stamps in a single table column.

3.5. Higher Precision in Binary and ASCII Tables: Quad Floating Point

For ASCII tables there may not be any need for a high-precision data type (see Section 3.3).

In binary tables, we expect that at some point a new data type will be defined, *long double* or *quad*. With the L and Q type codes spoken for, we propose that the value of TFORM n shall be *rSa* (suggesting sixteen bytes – or super-double); see Section 7.3.1 of the FITS Standard (2008) for the interpretation of this string. If and when this data type is adopted we shall assume that it will be used for time stamps and eventually supersede the use of doublet vectors (see Section 3.4).

3.6. Julian and Besselian Epochs

In a variety of contexts *epochs* are provided with astronomical data. Until 1976 these were commonly based on the Besselian year (see Section 4.3), with standard epochs B1900.0 and B1950.0. After 1976 the transition was made to Julian epochs based on the Julian year of 365.25 days, with the standard epoch J2000.0. They are tied to time scales ET and TDB, respectively.

B1950.0 corresponds to JD 2433282.423(ET); more epochs are provided by Seidelmann (1992) and they are scaled by the variable length of the Besselian year (see Section 4.3).

The Julian epochs are easier to calculate, as long as one keeps leap days in mind:

J2000.0 = 2000-01-01T12:00:00(TDB) = JD 2451545.00(TDB)
 J2001.0 = 2000-12-31T18:00:00(TDB) = JD 2451910.25(TDB)
 J2002.0 = 2002-01-01T00:00:00(TDB) = JD 2452275.50(TDB)
 J2003.0 = 2003-01-01T06:00:00(TDB) = JD 2452640.75(TDB)
 J2004.0 = 2004-01-01T12:00:00(TDB) = JD 2453006.00(TDB)

Caution: be aware that the year 1 corresponds to 1 CE, year 0 to 1 BCE, year -1 to 2 BCE, and so on. For negative year numbers there is an offset of one, since the (B)CE counting of years does not recognize a year 0.

4. Components of the Standard

This section describes the components of the standard. The keywords used to specify times are summarized in Table 4. The first section of the table contains data items: time values that have, in principle, global validity in the HDU. The second section presents metadata keywords that define the time reference frame for all time values in the HDU. If the HDU contains a table, all keywords in the first two sections may be replaced by columns, with specific values for each row (“Greenbank convention”). A subset of the metadata keywords may also be overridden in individual table columns, as summarized in the third section, while the fourth section lists the keywords that allow overriding the global HDU keyword values for the time axis in images.

In the following *high precision floating-valued* should be interpreted as *floating-valued* with the caveat that routine double floating precision may not provide sufficient accuracy; see Section 3. *Datetime-valued* should be interpreted as *string-valued* where the string conforms to ISO-8601 format as defined in Section 3.1 .

4.1. Keywords that Represent Global Time Values

Keywords The following time values may only be found in the header, independent of any time axes in the data. Except for DATE, they provide the top-level temporal bounds of the data in the HDU. As noted before, they may also be implemented as table columns.

DATE (datetime-valued)
 Creation date of the HDU in UTC

DATE-OBS (datetime-valued)
 Time of data in ISO-8601 according to TIMESYS

MJD-OBS (high precision floating-valued)
 Time of data in MJD according to TIMESYS

DATE-OBS is already defined in Section 4.4.2.2 of the FITS Standard. It is not specifically defined as the start time of the observation and has also been used to indicate some form of mean observing date and time. In order to specify a start date and time unambiguously one should use:

DATE-BEG (datetime-valued)
 Start time of data in ISO-8601 according to TIMESYS

DATE-AVG (datetime-valued)
 Average time of data in ISO-8601 according to TIMESYS; note: this paper does not prescribe how average times should be calculated

DATE-END (datetime-valued)
 Stop time of data in ISO-8601 according to TIMESYS

MJD-BEG (high precision floating-valued)
 Start time of data in MJD according to TIMESYS

MJD-AVG (high precision floating-valued)
 Average time of data in MJD according to TIMESYS; note: this paper does not prescribe how average times should be calculated

MJD-END (high precision floating-valued)
 Stop time of data in MJD according to TIMESYS

TSTART (high precision floating-valued)
 Start time of data in TIMEUNIT relative to MJDFREF, JDREF, or DATEREF according to TIMESYS

TSTOP (high precision floating-valued)
Stop time of data in TIMEUNIT relative to MJDREF, JDREF, or DATEREF according to TIMESYS

The following time values are part of an axis definition (see Section 5 for details):

CRVAL *i* (high precision floating-valued)
Reference pixel time value

CRVAL *ia* (high precision floating-valued)
Reference pixel time value

TCRVL *n* (high precision floating-valued)
Reference pixel time value

TCRV *na* (high precision floating-valued)
Reference pixel time value

Finally, Julian and Besselian epochs (see Sections 3.6 and 4.3) may be expressed by these two keywords – to be used with great caution:

JEPOCH (high precision floating-valued)
Julian epoch

BEPOCH (high precision floating-valued)
Besselian epoch

4.2. Time Coordinate Frame

This section defines the various components that constitute the time coordinate frame. For a full review of the IAU resolutions concerning space-time coordinate transformations, see Soffel et al. (2003).

4.2.1. Time Scale

The time scale defines the temporal reference frame (in the terminology of the IVOA Space-Time Coordinate metadata standard; see Rots 2008). See also the USNO (2008) page on time scales.

Table 1 lists recognized values. For a detailed discussion of the time scales we refer to Appendix A; that information will be of particular relevance for high-precision timing. In cases where this is significant, one may append a specific realization, in parentheses, to the values in the table; e.g., TT(TAI), TT(BIPM08), UTC(NIST). Note that linearity is not preserved across all time scales. Specifically, if the reference position remains unchanged (see Section 4.2.2), the first nine are linear transformations of each other (excepting leap seconds), as are TDB and TCB. Linearity is virtually guaranteed since images and individual table columns do not allow more than one reference position to be associated with them and since there is no overlap between reference positions that are meaningful for the first nine time scale on the one hand, and for the barycentric ones on the other. All use of the time scale GMT in FITS files shall be taken to have its zero point at midnight, conformant with UT, including dates prior to 1925; see Sadler (1978).

Any other time scales that are not listed in Table 1 are intrinsically unreliable and/or ill-defined. These should be tied to one of the existing scales with appropriate specification of the uncertainties; the same is true for free-running clocks. However, a local time scale, such as MET (Mission Elapsed Time) or OET (Observation Elapsed Time), may be defined for practical reasons. The Time Reference Value (see Section 4.2.3) should not

Table 1 Recognized Time Scale Values^{1,2}

TT	(Terrestrial Time; IAU standard): defined on the rotating geoid
TDT	(Terrestrial Dynamical Time): synonym for TT (deprecated)
ET	(Ephemeris Time): continuous with TT; should not be used for data taken after 1984-01-01
TAI	(International Atomic Time): TT – 32.184 s
IAT	synonym for TAI (deprecated)
UTC	(Universal Time, Coordinated; default): runs synchronously with TAI, except for the occasional insertion of leap seconds; as of 2009-01-01 UTC = TAI – 34 s
GPS	(Global Positioning System): runs (approximately) synchronously with TAI; GPS ≈ TAI – 19 s.
TCG	(Geocentric Coordinate Time): TT reduced to the geocenter, corrected for the relativistic effects of the Earth's rotation and gravitational potential; TCG runs faster than TT at a constant rate.
GMT	(Greenwich Mean Time): continuous with UTC; should not be used after 1972-01-01.
TDB	(Barycentric Dynamical Time): runs quasi-synchronously with TT, except for the relativistic effects introduced by variations in the Earth's velocity relative to the barycenter; when referring to celestial observations, a pathlength correction to the barycenter may be needed which requires the Time Reference Direction used in calculating the pathlength correction.
TCB	(Barycentric Coordinate Time): TDB corrected for the relativistic effects of the gravitational potential at the barycenter (relative to that on the rotating geoid), thus ensuring consistency with fundamental physical constants; TCB runs faster than TDB at a constant rate.
LOCAL	for simulation data and for free-running clocks.

¹Specific realizations may be appended to these values, in parentheses; see text.

²Recognized values for TIMESYS, CTYPE *ia*, TCTYP *n*, TCTY *na*.

be applied to the values and we strongly recommend that such timescales be provided as alternate time scales, with a defined conversion to a recognized time scale.

Most current computer operating systems adhere to the POSIX standard for time, and use Network Time Protocol (NTP) to closely synchronize to UTC. This reasonable approximation to UTC is then commonly used to derive timestamps for FITS data. However, authors of FITS writers and subsequent users of FITS timing information should be aware of the accuracy limitations of POSIX and NTP, especially around the time of a leap second.

Keywords The following keywords may assume the values for the time scale that are listed in Table 1. In addition, for backward compatibility, all except TIMESYS may also assume the value TIME (case-insensitive). The foundational keyword for the time scale is:

TIMESYS (string-valued)
Time Scale; default UTC

In relevant context it may be overridden by (see Sections 5.2 and 5.3 for details):

CTYPE *i* (string-valued)

Table 2 Standard Time Reference Position Values Contained in the JPL Ephemerides¹

TOPOCENTER	Topocenter: the location from where the observation was made (default)
GEOCENTER	Geocenter
BARYCENTER	Barycenter of the Solar System
RELOCATABLE	Relocatable: to be used for simulation data only
CUSTOM	A position specified by coordinates that is not the observatory location
Less common allowed standard values are:	
HELIOCENTER	Heliocenter
GALACTIC	Galactic center
EMBARYCENTER	Earth-Moon barycenter
MERCURY	Center of Mercury
VENUS	Center of Venus
MARS	Center of Mars
JUPITER	Barycenter of Jupiter
SATURN	Barycenter of Saturn
URANUS	Barycenter of Uranus
NEPTUNE	Barycenter of Neptune
PLUTO	Barycenter of Pluto

¹Recognized values for TREFPOS, TRPOS*n*; may be truncated to 8 characters

CTYPE *ia* (string-valued)

TCTYP *n* (string-valued)

TCTY *na* (string-valued)

The default value is UTC. Note that the time Scale for time axes is encoded in the CTYPE family of keywords; if these are absent or have the value TIME, it defaults to the value of TIMESYS; if that is absent, too, the time scale is UTC. See also the notes relating to these keywords in Sections 5 and 5.3.

4.2.2. Time Reference Position

The reference position specifies the spatial location at which the time is valid; i.e., where the time was measured or to which the observations were reduced. This may be a standard location (such as GEOCENTER or TOPOCENTER) or a point in space defined by specific coordinates. In the latter case one should be aware that a (3-D) spatial coordinate frame needs to be defined that is likely to be different from the frame(s) that the data are associated with. Note that TOPOCENTER is only moderately informative if no observatory location is provided or indicated.

The commonly allowed standard values are shown in Table 2. Note that for the gaseous planets we use the barycenters, for obvious reasons. Our preference is to spell the location names out in full, but in order to be consistent with the practice of Paper III (2006) and the FITS Standard (IAU FWG 2008) the values are allowed to be truncated to eight characters.

Some caution is in order, here. Time scales and reference positions cannot be combined arbitrarily if one wants a clock that runs linearly at TREFPOS. Table 3 provides a summary of compatible combinations. BARYCENTER should only be used in conjunction with time scales TDB and TCB and should be the only reference position used with these time scales. GEOCENTER, TOPOCENTER (as long as one does not venture too far from the earth's orbit), and EMBARYCENTER are appropriate for the first

Table 3 Compatibility of Time Scales and Reference Positions¹

Reference Position	TT, TDT, ET TAI, IAT GPS UTC, GMT	TCG	TDB	TCB	LOCAL
TOPOCENTER	t	ls			
GEOCENTER	ls	c			
EMBARYCENTER	ls	ls			
BARYCENTER			ls	c	
RELOCATABLE					c
Other ²	re	re			

¹Legend (combination is not recommended if no entry):

c: correct match

t: correct match on earth's surface, otherwise usually linear scaling

ls: linear relativistic scaling

re: non-linear relativistic scaling

²All other locations in the solar system

nine time scales in Table 1, although one needs to be aware that relativistic effects introduce a (generally linear) scaling in certain combinations; highly eccentric spacecraft orbits are the exception. Problems mainly arise when using a reference position on another solar system body (including HELIOCENTER). At this point we recommend synchronizing the local clock with one of the time scales defined on the earth's surface, TT, TAI, GPS, or UTC (in the last case: beware of leap seconds). Locally, such a clock will not appear to run at a constant rate, because of variations in the gravitational potential and in motions with respect to earth, but the effects can be calculated and are probably small compared to errors introduced by the alternative: establishing a local time standard.

In order to provide a complete description, TOPOCENTER requires the observatory's coordinates to be specified. We offer three options: the ITRS Cartesian coordinates (X, Y, Z) introduced in Paper III; a geodetic latitude/longitude/height triplet; or a reference to an orbit ephemeris file.

A non-standard location indicated by CUSTOM will be specified in a manner similar to the specification of the observatory location (indicated by TOPOCENTER). One should be careful with the use of the CUSTOM value and not confuse it with TOPOCENTER, as use of the latter imparts additional information on the provenance of the data.

Keywords The time reference position is specified by the keyword

TREFPOS (string-valued)

Time reference position; default TOPOCENTER

TREFPOS² will apply to time coordinate axes in images as well. See Section 5.2.1 for an explanation.

In binary tables different columns may represent completely different Time Coordinate Frames. However, each column can have only one time reference position, thus guaranteeing linearity (see Section 4.2.1) and the following keyword may override TREFPOS:

² The OGIP convention uses the keyword TIMeref and only allows values 'LOCAL' (i.e., Topocenter), 'GEOCENTRIC', 'HELIOCENTRIC', 'SOLARSYSTEM' (i.e., Barycenter); the convention contains also the somewhat peculiar keyword TASSIGN. We will not adopt these keywords in order to avoid confusion on allowed values and meaning. Instead, we adopt the keywords TREFPOS and TRPOS*n*.

TRPOS n (string-valued)

If the value of any of these keywords is TOPOCENTER, the observatory position needs to be specified. If the value is CUSTOM, the “custom” position needs to be specified. In either case we allow three mechanisms for this.

The ITRS Cartesian coordinates (with respect to the geocenter) as defined in Paper III:

OBSGEO-X (floating-valued)
ITRS Cartesian X in m

OBSGEO-Y (floating-valued)
ITRS Cartesian Y in m

OBSGEO-Z (floating-valued)
ITRS Cartesian Z in m

Similarly defined geodetic coordinates:

OBSGEO-B (floating-valued)
Latitude in deg, North positive

OBSGEO-L (floating-valued)
Longitude in deg, East positive

OBSGEO-H (floating-valued)
Altitude in m

An orbit ephemeris file:

OBSORBIT (string-valued)
URI, URL, or name of orbit ephemeris file

Beware that only one set of coordinates is allowed in a given HDU. Nanosecond precision in timing requires that OBSGEO- $[XYZBLH]$ be expressed in a geodetic reference frame defined after 1980 in order to be sufficiently accurate. The geodetic altitude OBSGEO-H is measured with respect to IAU 1976 ellipsoid which is defined as having a semi-major axis of 6378140 m and an inverse flattening of 298.2577. One should not assume a spherical earth!

4.2.3. Time Reference Value

We allow the time reference point to be defined in three different systems: ISO-8601, Julian Date (JD; see Herschel 1851), or Modified Julian Date (MJD = JD - 2,400,000.5; see IAU 1997). These reference values are only to be applied to time values associated with one of the recognized time scales listed in Table 1.

Keywords The reference point in time, to which all times in the HDU are relative, may be specified through one of three keywords:

MJDREF (high precision floating-valued)
Reference time in MJD

JDREF (high precision floating-valued)
Reference time in JD

DATEREF (datetime-valued)
Reference time in ISO-8601

If, for whatever reason, a header contains more than one of these keywords, JDREF shall have precedence over DATEREF and MJDREF shall have precedence over both the others. If none of the three keywords is present, there is no problem as long as all times in the HDU are expressed in ISO-8601; otherwise MJDREF = 0.0 shall be assumed. If TREFPOS = 'CUSTOM' it is legitimate for none of the reference time keywords to be present, as one may assume that we are dealing with simulation data.

Note: The *value* of the reference time has global validity for all time values, but it does not have a particular time scale associated with it.

Therefore, if MJDREF = 50814.0 and TIMEUNIT = 's':

a time instant $T = 86400.0$ associated with TT will fall on

1998-01-02T00:00:00.0(TT) or

1998-01-01T23:59:27.816(TAI),

but a time instant $T = 86400.0$ associated with TAI will fall on

1998-01-02T00:00:32.184(TT) or

1998-01-02T00:00:00.0(TAI).

4.2.4. Time Reference Direction

If any pathlength corrections have been applied to the time stamps (i.e., if the reference position is not TOPOCENTER for observational data), the reference direction that is used in calculating the pathlength delay should be provided in order to maintain a proper analysis trail of the data. However, this is only useful if there is also information available on the location from where the observation was made (the observatory location). The direction will usually be provided in a spatial coordinate frame that is already being used for the spatial metadata, although that is not necessarily the case. It is, for instance, quite conceivable that multiple spatial frames are already involved: spherical ICRS coordinates for celestial positions, and Cartesian FK5 for spacecraft ephemeris. We also acknowledge that the time reference direction does not by itself provide sufficient information to perform a fully correct transformation; however, within the context of a specific analysis environment it should suffice.

The uncertainty in the reference direction affects the errors in the time stamps. A typical example is provided by barycentric corrections where the time error t_{err} is related to the position error pos_{err} :

$$t_{err}(\text{ms}) \leq 2.4 pos_{err}(\text{arcsec})$$

We shall indicate the reference direction through a reference to specific keywords. These keywords may hold the reference direction explicitly or indicate columns holding the coordinates. In event lists where the individual photons are tagged with a spatial position, those coordinates may have been used for the reference direction and the reference will point to the columns containing these coordinate values. The *de facto* OGIP convention, on the other hand, uses the keywords RA_NOM and DEC_NOM indicating a globally applied direction for the entire HDU.

Keywords The time reference position is specified by the keyword

TREFDIR (string-valued)
Pointer to time reference direction

TREFDIR will apply to time coordinate axes in images as well. See Section 5.2.1 for an explanation.

In binary tables different columns may represent completely different Time Coordinate Frames. However, also in that situation the condition holds that each column can have only one Time Reference Direction. Hence, the following keyword may override TREFDIR:

TRDIR n (string-valued)

The value of the keyword shall consist of the name of the keyword or column containing the longitudinal coordinate, followed by a comma, followed by the name of the keyword or column

containing the latitudinal coordinate. For the above quoted OGIP convention this would result in:

TREFDIR = 'RA_NOM, DEC_NOM'

For the example in Table 6:

TRDIR20 = 'EventRA, EventDEC'

CUNIT i (string-valued)

CUNIT ia (string-valued)

TCUNI n (string-valued)

TCUN na (string-valued)

4.2.5. Planetary and Solar System Ephemeris

If applicable, the Planetary and Solar System ephemeris used for calculating pathlength delays should be identified. This is particularly pertinent when the time scale is TDB.

The ephemerides that are currently in use are JPL's (JPL 2007a and 2007b):

- DE200 (Standish 1990; considered obsolete, but still in use)
- DE405 (Standish 1998; default)
- DE421 (Folkner et al. 2008)

Future ephemerides will be accepted and recognized as they are released.

Keyword The Planetary and Solar System ephemeris used for the data (if required) is indicated by the value of the keyword

PLEPHEM (string-valued)

Solar System ephemeris; default DE405

4.3. Time Unit

The specification of the time unit allows the values defined in Paper I (2002) and the FITS Standard (IAU FWG 2008), with the addition of the century. We would recommend the following:

- s: second (default)
- d: day (= 86,400 s)
- a: (Julian) year (= 365.25 d)
- cy: (Julian) century (= 100 a)

The following values are also acceptable:

- min: minute (= 60 s)
- h: hour (= 3600 s)
- yr: (Julian) year (= a = 365.25 d)
- ta: tropical year
- Ba: Besselian year

The use of ta and Ba is not encouraged, but there are data and applications that require the use of tropical years or Besselian epochs. The length of the tropical year ta in days is (McCarthy & Seidelmann (2009)):

$$365.2421896698 - 0.00000615359T - 7.29 \times 10^{-10}T^2 + 2.64 \times 10^{-10}T^3$$

where T is in Julian centuries since 2000-01-01T00:00:00(TT). The length of the Besselian year Ba in days is (ibid.):

$$365.0941896698 - 0.14800615359T - 7.29 \times 10^{-10}T^2 + 2.64 \times 10^{-10}T^3$$

Keywords The time unit is set by the keyword

TIMEUNIT (string-valued)

Time unit; default s

In relevant context, this may be overridden by (see Section 5 for details):

4.4. Assorted Items Affecting Time Data: Corrections, Errors, etc.

All quantities enumerated below will be expressed in the prevailing time units, the default being s.

4.4.1. Time Offset

It is sometimes convenient to be able to apply a uniform clock correction in bulk by just putting that number in a single keyword. A second use for a time offset is to set a zero offset to a relative time series, allowing zero-relative times, or just higher precision, in the time stamps. Its default value is zero.

Its value is to be added to MJDREF, JDREF, or DATeref, and hence affects the values of TSTART, TSTOP, and the time axis reference values (CRVAL i , c.s.), as well as any time pixel values in a binary table.

Keyword The time offset is set by:

TIMEOFFS (high precision floating-valued)

Time offset; default 0.0

and has global validity for all times in the HDU. It has the same meaning as the keyword TIMEZERO in the OGIP convention – which we did not adopt out of concern for the potentially ambiguous meaning of the name. The net effect of this keyword is that the value of TIMEOFFS is to be added to the time stamp values in the file. Formally, this is effected by adding that value to MJDREF, JDREF, and/or DATeref.

4.4.2. Absolute Error

The absolute time error is the equivalent of the systematic error defined in previous papers.

Keywords The absolute time error is set by:

TIMSYER (floating-valued)

Absolute time error

but may be overridden, in appropriate context, by (see Section 5 for details):

CSYER (floating-valued)

CSYER ia (floating-valued)

TCSYEn (floating-valued)

TCSYna (floating-valued)

4.4.3. Relative Error

The relative time error specifies accuracy of the time stamps relative to each other. This error will usually be much smaller than the absolute time error. This error is equivalent to the random error defined in previous papers.

Keywords The relative time error (the random error between time stamps) is set by:

`TIMRDER` (floating-valued)
Relative time error

but may be overridden, in appropriate context, by (see Section 5 for details):

`CRDER` (floating-valued)

`CRDERia` (floating-valued)

`TCRDEn` (floating-valued)

`TCRDna` (floating-valued)

4.4.4. Time Resolution

The resolution of the time stamps is represented by a simple double. This may, for instance, be the size of the bins for time series data or the bit precision of the time stamp values.

Keyword The time resolution is global in the HDU, and set by the keyword

`TIMEDEL` (floating-valued)
Time resolution

in the units of `TIMEUNIT`.

4.4.5. Time Binning

When data are binned in time bins (or, as a special case, events are tagged with a time stamp of finite precision) it is important to know to which position in the bin (or pixel) that time stamp refers. This is an important issue: the FITS standard assumes that coordinate values correspond to the center of all pixels; yet, clock readings are effectively truncations, not rounded values, and therefore correspond to the lower bound of the pixel.

Keyword The relative position of the time stamp in each time bin (`TIMEDEL` in the case of an event list) or pixel (`CDELTA` in the case of an image axis) is set universally in the HDU by the keyword:

`TIMEPIXR` (floating-valued)
Pixel position of the time stamp; from 0.0 to 1.0, default 0.5.

In conformance with the FITS pixel definition, the default is 0.5, although the value 0.0 may be more common in certain contexts. Note, for instance, that this is required when truncated clock readings are recorded, as is the case for almost all event lists. It seems unwise to allow this keyword to be specified separately for multiple time frames, rather than requiring its value to apply to all.

4.5. Durations

Durations shall not be expressed in ISO-8601 format, but only as actual durations (i.e., numerical values) in the units of the specified time unit.

There is an extensive collection of header keywords that indicate time durations, such as exposure times, but there are many pitfalls and subtleties that make this seemingly simple concept treacherous. One may encounter similar-sounding keywords for

concepts like: awarded exposure time; scheduled exposure time; on-target time; duration of the exposure, including dead time and lost time; exposure time charged against the awarded exposure time; exposure time corrected for lost (bad) data; and exposure time corrected for dead time. Related to these are various keywords providing dead time correction factors, dead time correction flags, and duty cycle information, `TELAPSE`, as well as Good-Time-Interval (GTI) tables. We suggest that these are excellent candidates for definition through an appropriate formally approved FITS convention, rather than inclusion in this standard.

We shall only define `XPOSURE` and `TELAPSE` in the present standard.

Keyword The only defined durations are indicated by the keywords:

`XPOSURE` (floating-valued)

in the units of `TIMEUNIT`. It shall be the effective exposure time for the data, corrected for dead time and lost time. If the HDU contains multiple time slices, it shall be the total accumulated exposure time over all slices. More obvious candidates for the keyword name (like `EXPOSURE`) had to be avoided since they have been used with conflicting definitions in various sub-communities.

`TELAPSE` (floating-valued)

also in the units of `TIMEUNIT` provides the amount of time elapsed between the start (`TSTART`, `MJD-BEG`, etc.) and the end (`TSTOP`, `DATE-END`, etc.) of the observation or data stream.

4.6. Good Time Interval (GTI) Tables

Good-Time-Interval (GTI) tables are indispensable for data with “holes” in them, especially photon event files, as they allow one to discriminate between “no data received” *versus* “no data taken”. GTI tables contain two mandatory columns, `START` and `STOP`, and one optional column, `WEIGHT`. The first two define the interval, the third, with a value from 0 to 1, the quality of the interval; *i.e.*, a weight of 0 indicates a *Bad-Time-Interval*. `WEIGHT` has a default value of 1. Any time interval not covered in the table shall be considered to have a weight of zero.

5. Usage Contexts

Before getting to specific usage context, we need to make a few general comments.

First, we should point out that the distortion conventions described in Paper IV (2012) are also very much applicable to the time coordinate axis. The keywords that are discussed in the following in detail are summarized in Table 4.

Second, the globally applicable keywords like `TIMESYS`, `MJDREF` et al., `TIMEUNIT`, etc., provide default values for the corresponding `C*` and `TC*` keywords in images and tables with `CTYPE` or `TTYPE` set to `TIME`. Furthermore, with the exception of `TIMESYS` itself, they provide defaults for all axis and column specifications (including alternate coordinate definitions) that use a time scale listed in Table 1. Any alternate coordinate specified in a non-recognized time scale assumes the value of the axis pixels or the column cells, optionally modified by applicable scaling and/or reference value keywords.

Finally, we have observed that there is a confusing variation in the labeling of time axes in figures and presentations. In

particular, the usage of terms like “TJD”, “HJD”, and “BJD” is highly ambiguous. Julian and Modified Julian Date counts do not imply any particular time scale or any particular reference position. The “B” in “BJD” raises the question whether it refers to the reference position BARYCENTER or the time scale TDB. And an expression like “BJD–2400000” leaves the reader in doubt whether the value is to be taken literally or whether the author really meant “BJD–2400000.5”. We strongly recommend that authors be explicit about the times that are posted and adopt the following convention for axis labeling:

```
JD|MJD(<times scale>;<reference position>
```

In order to facilitate the correct labeling we suggest that these strings be provided in the CNAME* and TCNA* keywords if possible; for instance:

```
TCNAM1 = 'MJD(TDB;Barycenter)'
```

Also, see the examples of TCNA1E and TCNA1F in Table 8.

5.1. Header Keywords

The rules governing these keywords are elaborated on in Section 4 and summarized in Table 4.

5.2. Time Axis in Images

Example 1 (Table 5) is a data cube in which the 3rd axis is time. It is in fact a sequence of 2-D images stacked together.

The rules governing keywords defining the time axis in an image (which could be a one-dimensional time series or a multi-dimensional space-time-spectral hypercube) are also largely being dealt with in Section 4 and summarized in Table 4, but there are some aspects that require further elaboration as presented in the following sub-sections.

5.2.1. Restrictions

An image will have at most one time axis as identified by having the CTYPE i value of TIME or one of the values listed in Table 1. Consequently, as long as the axis is identified through CTYPE i , there is no need to have axis number identification on the global time-related keywords. In addition, we expressly prohibit the specification of multiple time reference positions on this axis for alternate time coordinate frames, since this would give rise to complicated model-dependent non-linear relations between these frames. Hence, time scales TDB and TCB may be specified in the same image, but cannot be combined with any of the first nine time scales in Table 1; those first nine can be expressed as linear transformations of each other, too, provided the reference position remains unchanged. Time scale LOCAL is by itself, intended for simulations, and should not be mixed with any of the others.

5.2.2. CDELT ia , CD i_{-ja} and PC i_{-ja}

If the image does not use a matrix for scaling, rotation and shear (Paper I, 2002), CDELT ia provides the numeric value for the time interval.

If the PC form of scaling, rotation and shear (Paper I, 2002) is used, CDELT ia provides the numeric value for the time interval, and PC i_{-j} , where $i = j =$ the index of the time axis (in the typical case of an image cube with axis 3 being time, $i = j = 3$) would take the exact value 1, the default (Paper I, 2002).

When the CD i_{-j} form of mapping is used, CD i_{-j} provides the numeric value for the time interval.

If one of the axes is time and the matrix form is used, then the treatment of the PC i_{-ja} (or CD i_{-ja}) matrices involves at least a Minkowsky metric and Lorentz transformations (as contrasted with Euclidean and Galilean). See Soffel et al. (2003) for a full review of the IAU resolutions concerning space-time coordinate transformations.

As an example we present a header in Table 6 (Example 2) that describes a SOHO Coronal Diagnostic Spectrometer observation from October 1998: a linear slit moves across the field from right to left during the observation, so different parts (columns) of the image are observed at different times. The example header defines the relations between the different coordinate systems by specifying a degenerate Time axis that is related to the first spatial pixel axis through a PC i_{-j} matrix; the non-diagonal spatial elements are not zero since the detector was not aligned to solar north.

An alternative approach would be to define the Time axis as CTYPE2A tying it directly to the almost-longitude pixel coordinate.

If we align the image to solar north, the header changes to what is shown in Example 3 (Table 7). One could still use the alternative description of Time as an alternate axis on longitude, but in that case it would need its own PC 2_{-jA} matrix.

5.2.3. CRVAL ia

The WCS standard requires this keyword to be numeric and cannot be expressed in ISO-8601 format. Therefore, CRVAL ia is required to contain the elapsed time in units of TIMEUNIT or CUNIT ia , even if the zero point of time is specified by DATEREF.

5.3. Time Columns in Tables

Example 4 (Table 8) is part of the header of an event list (a binary table in pixel list mode) with two time columns. Column 1 carries time in TT, with alternate time coordinate frames in UTC, TCG, Mission Elapsed Time, Observation Elapsed Time, MJD, and JD. Column 20 contains the time stamps in TDB with alternate frames in TCB and Julian epoch; columns 21 and 22 provide the events' positions.

The rules governing keywords defining the time in table columns (pixel as well as vector columns) are largely being dealt with in Section 4 and summarized in Table 4, but, again, there are some aspects that require further elaboration.

All times (other than ISO-8601), expressed in a recognized time scale (see Table 1), are relative (to MJDREF, JDREF or DATEREF). That means that they are elapsed times and that users have to take care of leap seconds when using UTC; the unit 'd' is defined as 86400 elapsed seconds. But beware of the following: the reference time values are to be taken in the time scale specified for the coordinate one is dealing with. That is why the TCRV1A in the Table 8 needs to account for the difference between MJDREF(TT) and MJDREF(UTC).

Times that are expressed in any other time scale (e.g., Mission Elapsed Time, a common scale) take the values in the table cells at face value, though they may be modified by applicable keywords such as TCRP*, TCRV*, and TCD*.

In the context of tables the most important point to keep in mind is that TCTYP n and/or TCTY na contain the time scale. However, it should also be pointed out that a binary table column with TTYPE $n =$ 'TIME' and either lacking any TC* n keywords or with TC* $n =$ 'TIME' will be controlled by the global keywords

listed in Table 4. This is a common convention in existing files that will still be compliant with the present standard.

The keywords JEPOCH and BEPOCH, of course, may also be turned into table columns. However, one should be mindful that they are implicitly tied to specific time scales and represent absolute times. Consequently, they have no association with any of the global keywords.

5.3.1. Restrictions

The same restrictions imposed on the image time axis (see Section 5.2.1) also apply to individual table columns. However, since one can have more than one column with time information in the same table, it is possible to mix different time reference positions and time scales that are not linearly related to each other – provided that one does not mix these in the same column.

5.4. Time in Random Groups

There are two ways in which time can enter into random group data (see Greisen & Harten 1981): as one of the subarray axes or through a group parameter. In the former case the situation is identical to that in images and we refer to Section 5.2 for the rules. If time is to be transmitted through a group parameter, it simply means that the

PTYPE*i* (string-valued)

keyword needs to be set to one of the time scale codes from Table 1, just like the CTYPE*i*. All the global time reference frame keywords (see Table 4) apply, just as they would if CTYPE*i* were set to the same time scale value, except that there is no possibility of override since the PUNIT*i*, PSYER*i*, and PRDER*i* keywords are not defined in the standard.

6. Concluding Remarks on Precision

The following comments summarise some salient points that may otherwise go unnoticed.

Times have special requirements when it comes to precision and, hence, data types. We anticipate at some time in the future that one or two new data types may be added to the FITS standard that will address this requirement. In the meantime,

As an alternative to a 128 bit quad floating point (IEEE 754-2008) we recommend that relative elapsed times may be expressed as 2D, but require that the first element of the 2D doublet vector contain the integer part, the second the fractional part of time. This is, in a way, an unfortunate bandaid, but not unprecedented, since the device is used in various ephemeris and timing packages.

There is no precision problem with time-related keywords, as they may contain as many digits as necessary. However, users should take special care in reading these values and not simply assume that "a double is good enough".

Times are relative (to MJDREF, JDREF or DATEREF), except when they are expressed as an ISO-8601 *datetime* string.

Acknowledgements. The authors want to express their deep gratitude and appreciation for the dedication and tireless efforts of their colleague and friend Peter Bunclark in moving the work on this paper forward. We received his last email on 8 December 2008, just two days before his untimely death. We miss Pete dearly, not only as a great co-author who kept us on the straight and narrow, but especially as a very good friend. It was a privilege to have collaborated with him. We are also very much indebted to IAU FITS Working Group chair Bill Pence, who provided valuable comments and kept exhorting us to finally finish this paper. AHR gratefully acknowledges the many helpful discussions he had with Jonathan McDowell.

References

- Bunclark, P. S. & Rots, A. H. 1997 FITS-Y2k agreement: <http://fits.gsfc.nasa.gov/year2000.html>
- Calabretta, M. R., & Greisen, E. W. 2002, A&A 395, 1077, Paper II
- Calabretta, M. R., et al. 2012, Representations of distortions in FITS world coordinate systems, in preparation, Paper IV
- Clemence, G. M. 1948, AJ 53, 169
- Folkner, W. M., Williams, J. G., Boggs, D. H. 2008, JPL Memo IOM 343.R-08-003: ftp://naif.jpl.nasa.gov/pub/naif/generic_kernels/spk/planets/de421-announcement.pdf
- Fukushima, T., et al. 2008, Transactions of the International Astronomical Union, Series A, 27, 5
- Gregorius P. P. XIII 1582 *Inter gravissimas*, in: Clavius, C. *Romani Calendarii A Gregorio XIII P. M. Restituti*, Rome 1603; see also: http://www.fourmilab.ch/documents/calendar/IG_Latin.html
- Greisen, E. W., & Calabretta, M. R. 2002, A&A 395, 1061, Paper I
- Greisen, E.W., Calabretta, M.R. Valdes, F.G., & Allen, S.L., 2006, Paper III: Representations of spectral coordinates in FITS, A&A 446, 747-771.
- Greisen, E. W. & Harten, R. H. 1981, A&ASuppl 44, 371
- Herschel, John 1851, *Outlines of astronomy* (4th edition) by Sir John F. W. Herschel
- IAU 1997, Resolution B1 of the XXIIIrd IAU, http://www.iau.org/static/resolutions/IAU1997_French.pdf <http://www.iers.org/MainDisp.csl?pid=98-110>
- IAU FITS Working Group, 2008 Definition of the Flexible Image Transport System (FITS) http://fits.gsfc.nasa.gov/fits_standard.html
- Irwin, A. W. & Fukushima, T. A. 1999, A&A 348, 642
- McCarthy, D. D. & Seidelmann, P. K. 2009, *TIME – From Earth Rotation to Atomic Physics*, Wiley-VCH
- NASA/JPL Planetary Ephemerides 2007a: <http://ssd.jpl.nasa.gov/?ephemerides>
- NASA/JPL Solar and Planetary Ephemerides 2007b: http://ssd.jpl.nasa.gov/?planet_eph_export
- OGIP/GSFC/NASA FITS conventions: http://heasarc.gsfc.nasa.gov/docs/heasarc/ofwg/ofwg_recomm.html
- Rots, A. H. 2008 Space-Time Coordinate Metadata for the Virtual Observatory: <http://www.ivoa.net/Documents/latest/STC.html>
- Sadler, D. H. 1978, QJRAS 19, 290
- Seidelmann, P. K. 1992, *Explanatory Supplement to the Astronomical Almanac*, University Science Books
- Seidelmann, P. K. & Fukushima, T. 1992, A&A 265, 833
- Soffel, M. et al. 2003, AJ 126, 2687
- Standish, E. M. 1990, A&A 233, 252
- Standish, E. M. 1998, JPL Memo IOM 312.F-98-048
- USNO Time Scales: <http://tycho.usno.navy.mil/systime.html>

Table 4. Time Scale Keywords

Keyword Description	Section	Header Only	Images		Table Pixel Columns		Table Vector Columns	
			Single	Multiple	Primary	Alternate	Primary	Alternate
Informational Keywords (data)								
Date of HDU creation ^a	4.1	DATE						
Date/time of whole observation	4.1	DATE-OBS MJD-OBS						
Effective date/Time of observation	4.1	DATE-AVG MJD-AVG						
Start date/time of observation	4.1	DATE-BEG MJD-BEG TSTART						
End date/time of observation	4.1	DATE-END MJD-END TSTOP						
Net exposure time	4.5	XPOSURE						
Wall clock exposure time	4.5	TELAPSE						
Global Time Reference Frame Keywords (metadata)								
Time scale	4.2.1	TIMESYS						
Zero point in MJD	4.2.3	MJDREF						
Zero point in JD	4.2.3	JDREF						
Zero point in ISO-8601	4.2.3	DATEREF						
Reference position	4.2.2	TREFPOS						
Reference direction	4.2.4	TREFDIR						
Solar System ephemeris	4.2.5	PLEPHEM						
Time unit	4.3	TIMEUNIT						
Time resolution	4.4.4	TIMEDEL						
Time offset	4.4.1	TIMEOFFS						
Time location in pixel	4.4.5	TIMEPIXR						
Absolute Error	4.4.2	TIMSYER						
Relative Error	4.4.3	TIMRDER						
Optional Context-Specific Override Keywords for Metadata								
Time scale	4.2.1	TIMESYS	CTYPE <i>i</i>	CTYPE <i>ia</i>	TCTYP <i>n</i>	TCTY <i>na</i>	iCTYP <i>n</i>	iCTY <i>na</i>
Reference position	4.2.2	TREFPOS				TRPOS <i>n</i>		TRPOS <i>n</i>
Reference direction	4.2.4	TREFDIR				TRDIR <i>n</i>		TRDIR <i>n</i>
Time unit	4.3	TIMEUNIT	CUNIT <i>i</i>	CUNIT <i>ia</i>	TCUNI <i>n</i>	TCUN <i>na</i>	iCUNI <i>n</i>	iCUN <i>na</i>
Absolute Error	4.4.2	TIMSYER	CSYER <i>i</i>	CSYER <i>ia</i>	TCSYE <i>n</i>	TCSY <i>na</i>	iCSYE <i>n</i>	iCSY <i>na</i>
Relative Error	4.4.3	TIMRDER	CRDER <i>i</i>	CRDER <i>ia</i>	TCRDE <i>n</i>	TCRD <i>na</i>	iCRDE <i>n</i>	iCRD <i>na</i>
Context-Specific Keywords for Metadata								
Time axis name	5.2		CNAME <i>i</i>	CNAME <i>ia</i>	TCNAM <i>n</i>	TCNA <i>na</i>	iCNAM <i>n</i>	iCNA <i>na</i>
Time axis reference pixel	5.2		CRPIX <i>i</i>	CRPIX <i>ia</i>	TCRPX <i>n</i>	TCRP <i>na</i>	iCRPX <i>n</i>	iCRP <i>na</i>
Time axis reference value	5.2		CRVAL <i>i</i>	CRVAL <i>ia</i>	TCRVL <i>n</i>	TCRV <i>na</i>	iCRVL <i>n</i>	iCRV <i>na</i>
Time scaling	5.2.2		CDEL <i>Ti</i>	CDEL <i>Tia</i>	TCDLT <i>n</i>	TCDE <i>na</i>	iDLT <i>n</i>	iCDE <i>na</i>
Transformation matrix	5.2.2		CD <i>i_j</i>	CD <i>i_ja</i>		TC <i>n_ka</i>		ijCD <i>na</i>
Transformation matrix	5.2.2		PC <i>i_j</i>	PC <i>i_ja</i>		TP <i>n_ka</i>		ijPC <i>na</i>

^aIn UTC if the file is constructed on the Earth's surface

Table 5. Cube with two spatial & one time axis

123456789	123456789	123456789	123456789	123456789	123456789	123456789	123456789
SIMPLE	=		T	/	Fits standard		
BITPIX	=		-32	/	Bits per pixel		
NAXIS	=		3	/	Number of axes		
NAXIS1	=		2048	/	Axis length		
NAXIS2	=		2048	/	Axis length		
NAXIS3	=		11	/	Axis length		
DATE	=	'2008-10-28T14:39:06'		/	Date FITS file was generated		
OBJECT	=	'2008 TC3'		/	Name of the object observed		
EXPTIME	=		1.0011	/	Integration time		
MJD-OBS	=		54746.02749237	/	Obs start		
DATE-OBS	=	'2008-10-07T00:39:35.3342'		/	Observing date		
TELESCOP	=	'VISTA'		/	ESO Telescope Name		
INSTRUME	=	'VIRCAM'		/	Instrument used.		
TIMESYS	=	'UTC'		/	From Observatory Time System		
TREFPOS	=	'TOPOCENT'		/	Topocentric		
MJDREF	=		54746.0	/	Time reference point in MJD		
RADESYS	=	'ICRS'		/	Not equinoctial		
CTYPE2	=	'RA---ZPN'		/	Zenithal Polynomial Projection		
CRVAL2	=		2.01824372640628	/	RA at ref pixel		
CUNIT2	=	'deg'		/	Angles are degrees always		
CRPIX2	=		2956.6	/	Pixel coordinate at ref point		
CTYPE1	=	'DEC--ZPN'		/	Zenithal Polynomial Projection		
CRVAL1	=		14.8289418840003	/	Dec at ref pixel		
CUNIT1	=	'deg'		/	Angles are degrees always		
CRPIX1	=		-448.2	/	Pixel coordinate at ref point		
CTYPE3	=	'UTC'		/	linear time (UTC)		
CRVAL3	=		2375.341	/	Relative time of first frame		
CUNIT3	=	's'		/	Time unit		
CRPIX3	=		1.0	/	Pixel coordinate at ref point		
CTYPE3A	=	'TT'		/	alternative linear time (TT)		
CRVAL3A	=		2440.525	/	Relative time of first frame		
CUNIT3A	=	's'		/	Time unit		
CRPIX3A	=		1.0	/	Pixel coordinate at ref point		
OBSGEO-B	=		-24.6157	/	[deg] Tel geodetic latitude (=North)+		
OBSGEO-L	=		-70.3976	/	[deg] Tel geodetic longitude (=East)+		
OBSGEO-H	=		2530.0000	/	[m] Tel height above reference ellipsoid		
CRDER3	=		0.0819	/	random error in timings from fit		
CSYER3	=		0.0100	/	absolute time error		
PC1_1	=		0.999999971570892	/	WCS transform matrix element		
PC1_2	=		0.000238449608932	/	WCS transform matrix element		
PC2_1	=		-0.000621542859395	/	WCS transform matrix element		
PC2_2	=		0.999999806842218	/	WCS transform matrix element		
CDELTA1	=		-9.48575432499806E-5	/	Axis scale at reference point		
CDELTA2	=		9.48683176211164E-5	/	Axis scale at reference point		
CDELTA3	=		13.3629	/	Axis scale at reference point		
PV1_1	=		1.	/	ZPN linear term		
PV1_3	=		42.	/	ZPN cubic term		
END							

Table 8. Header extract of a binary table (event list) with two time columns

```

123456789 123456789 123456789 123456789 123456789 123456789 123456789 123456789
-----

COMMENT      ----- Globally valid key words -----

TIMESYS = 'TT          ' / Time system REPEATED FOR CLARITY   ###
MJDREF  = 50814.000000000000 / MJD zero point for (native) TT   ###
MJD-BEG = 53516.157939301 / MJD start time in (native) TT     ###
TSTART  = 233466445.95561 / Start time in MET                  ###
TIMEPIXR= 0.50000000000000 / default                            ###
TIMEDEL = 3.24104000000000 / timedel Lev1 (in seconds)        ###
TREFPOS = 'TOPOCENT' / Time is measured at the telescope
PLEPHEM = 'DE405 ' / SS ephemeris that is used
TIMRDER = 1.00000000000000E-09 / Relative error
TIMSYER = 5.00000000000000E-05 / Absolute error
OBSORBIT= 'orbitf315230701N001_eph1.fits' / Orbit ephemeris file

COMMENT      ----- First Time Column -----

TTYPE1 = 'Time ' / S/C TT corresponding to mid-exposure   ###
TFORM1 = '2D ' / format of field                            ###
TUNIT1 = 's ' /                                           ###
TCTYP1 = 'TT '
TCNA1 = 'Terrestrial Time' / This is TT
TCUNI1 = 's '
TCRPX1 = 0.0 / MJDREF is the true zero point for TIME-TT ...
TCRVL1 = 0.0 / ...and relative time is zero there
TCDLT1 = 1.0 / 1 s is 1 s
TCRD1 = 1.00000000000000E-09 / Relative error
TCSY1 = 5.00000000000000E-05 / Absolute error

TCTY1A = 'UTC ' / UTC ELAPSED seconds since MJDREF
TCNA1A = 'Coordinated Universal Time' / This is UTC
TCUN1A = 's '
TCRP1A = 0.0
TCRV1A = 63.184
TCDE1A = 1.0

TCTY1B = 'TCG ' / TCG
TCNA1B = 'Geocentric Coordinate Time' / This is TCG
TCUN1B = 's ' / still in seconds
TCRP1B = 0.0 / MJDREF is the reference point
TCRV1B = 0.46184647 / But TCG is already ahead of TT at MJDREF
TCDE1B = 1.0000000006969290 / And it keeps running faster

TCTY1C = 'MET ' / Mission Elapsed Time
TCNA1C = 'Mission Elapsed Time' / This is MET

TCTY1D = 'OET ' / Observation Elapsed Time
TCNA1D = 'Observation Elapsed Time' / This is OET
TCRV1D = 0.0 / Reference pixel: 0 is at: ...
TCRP1D = 233466445.95561 / ... start time in MET

TCTY1E = 'MJD ' / For listing MJD
TCNA1E = 'MJD(TT;Topocenter)' / This allows a properly labeled MJD axis
TCUN1E = 's ' / Now in days

```

Table 8 (cont'd)

123456789	123456789	123456789	123456789	123456789	123456789	123456789	123456789
TCRP1E	= 0.0		/ MET 0 is the reference point				
TCRV1E	= 50814.0		/ Not surprising, that is MJDREF				
TCDE1E	= 1.157407407407e-05		/ = 1/86400				
TCTY1F	= 'JD	'	/ For listing JD				
TCNA1F	= 'JD(TT;Topocenter)'		/ This allows a properly labeled JD axis				
TCUN1F	= 's	'	/ Now in days				
TCRP1F	= 0.0		/ MET 0 is the reference point				
TCRV1F	= 2450814.5		/ Not surprising, that is JDREF				
TCDE1F	= 1.157407407407e-05		/ = 1/86400				
COMMENT	----- Second Time Column -----						
TTYPE20	= 'Barytime'		/ S/C TDB corresponding to mid-exposure				
TFORM20	= '2D	'	/ format of field				
TUNIT20	= 's	'					
TCTYP20	= 'TDB	'					
TRPOS20	= 'BARYCENT'		/ Time is measured at the Barycenter				
TRDIR20	= 'EventRA,EventDEC'		/ Reference direction is found in cols 21 and 22				
TCNA20	= 'Barycentric Dynamical Time'		/ This is TDB				
TCUN20	= 's	'					
TCRPX20	= 0.0		/ MJDREF is the true zero point for Barytime ...				
TCRVL20	= 0.0		/ ...and relative time is zero there				
TCDLT20	= 1.0		/ 1 s is 1 s				
TCRD20	= 1.0000000000000000E-09		/ Relative error				
TCSY20	= 5.0000000000000000E-05		/ Absolute error				
TCTY20C	= 'TCB	'	/ TCB				
TCNA20C	= 'Barycentric Coordinate Time'		/ This is TCB				
TCUN20C	= 's	'	/ still in seconds				
TCRP20C	= 0.0		/ MJDREF is the reference point				
TCRV20C	= 10.27517360		/ But TCB is already ahead of TDB at MJDREF				
TCDE20C	= 1.000000001550520		/ And it keeps running faster				
TCTY20G	= 'JEPOCH	'	/ JEPOCH				
TCNA20G	= 'Julian Epoch'		/ This is a proper Julian epoch				
TCUN20G	= 'a	'	/ now in Julian years				
TCRP20G	= 63115200		/ 2000-01-01T12:00:00 in MET seconds				
TCRV20G	= 2000.0		/ J2000.0				
TCDE20G	= 3.16880878141E-08		/ Convert seconds to Julian years				
COMMENT	----- RA and Dec of each photon event -----						
TTYPE21	= 'EventRA	'	/ RA of photon event				
TFORM21	= 'D	'	/ format of field				
TUNIT21	= 'deg	'					
TTYPE22	= 'EventDEC'		/ Dec of photon event				
TFORM22	= 'D	'	/ format of field				
TUNIT22	= 'deg	'					
END							

Appendix A: Time Scales

If one is dealing with high-precision timing, there are a more subtle issues associated with the various time scales that should be considered. This Appendix provides the necessary information that supplements Section 4.2.1. It also provides some background information on how some of the time scales are realized and how they relate to each other.

A.1. *TT and TDT*

TT is defined by Resolution B1.9 of the 24th General Assembly of the IAU in 2000 at Manchester³. This is a re-definition of TT as originally defined by Recommendation IV of Resolution A4 of the XXIst General Assembly of the IAU in 1991 at Buenos Aires⁴. By that resolution TT was recognized as a better-defined replacement for TDT.

The initial definition of TT was explained by Seidelmann & Fukushima (1992). For explanation of the redefinition see Petit in IERS Technical Note 29⁵.

Due to the rotation of the earth (and motion of other bodies), a point on the surface changes its depth in the gravitational potential of the solar system. As noted in Soffel et al. 2003, the proper time experienced by chronometers on the surface of earth differs from TT with a diurnal variation at the picosecond level.

Because TDT never had a satisfactory definition its meaning is ambiguous at microsecond precision. For most uses other than historical tabulation it is more practical to express such time stamps as TT.

A.2. *TCG and TCB*

TCG and TCB are defined by Recommendation III of Resolution A4 of the XXIst General Assembly of the IAU in 1991 at Buenos Aires⁶. Note 4 suggests that precise use of these time scales requires specification of both the realized time scale (i.e., TAI) and the theory used to transform from the realized time scale to the coordinate time scale. All of the references given above for TT are also relevant for TCG and TCB.

Given that TT and TCG differ only by a constant rate, a precise value of TCG is specified by documenting the realization of TT. Thus we suggest that TCG(TAI) be shorthand for TCG computed from TT = TAI + 32.184 s or, alternatively, TCG(TT(TAI)). Likewise, we suggest that TCG(BIPMnn) be shorthand for TCG(TT(BIPMnn)).

Specifying a precise value for TCB requires documenting a precise value of TT and additionally a time ephemeris. A current example of a time ephemeris is TE405 given by Irwin & Fukushima (1999).

It is not immediately clear to us how best to express this in a concise value for the FITS keyword, for there is no guarantee of a controlled vocabulary for the time ephemerides: nothing prevents other authors from producing another time ephemeris based on DE405. However we may proceed on the assumption that the differences between any two time ephemerides will be inconsequentially small. Consequently, we suggest that TCB(BIPMnn,TE405) be shorthand for TCB computed from TT(BIPMnn) and TE405.

A.3. *TDB*

TDB is defined by Resolution B3 of the XXVIth General Assembly of the IAU in 2006 at Prague⁷. This definition is required for microsecond precision.

A.4. *ET*

ET was defined by Clemence (1948) named by Resolution 6 of the 1950 Conference on the Fundamental Constants of Astronomy held at CNRS in Paris, and adopted by a recommendation from IAU Commission 4 during the VIIIth General Assembly in 1952 at Rome. The definition of ET is based on the works of Newcomb Tables of the Sun, Astr. Papers Amer. Ephemeris 6, 1895 and Brown Tables of the Motion of the Moon, 1919 At the IAU General Assemblies in 1961 and 1967 Commission 4 designated three improvements on ET named ET0, ET1, and ET2.

Because ET is nonrelativistic its meaning is ambiguous at millisecond precision. For most uses other than historical tabulation it is more practical to express such time stamps as TT or TDB. For the purposes of historical tabulation we might want to recommend the use of 'ET(ET0)', 'ET(ET1)', and 'ET(ET2)'.

A.5. *TAI*

TAI is defined by BIPM⁸. (SLA) This wants to be a little more formal for Paper V with references to the roles of the CCDS/CCTF, CIPM, BIPM, and CGPM. I believe that it is possible to cite material from members of the CCTF who have indicated that the definition of TAI has also been amended by the IAU 2000 resolution B1.9, but I don't have them in hand right now.)

Thus TAI is intended to be the best possible realization of TT, which means its aim is to be a geocentric coordinate time scale. Because of deficiencies in the realization, TAI is only approximately equal to TT - 32.184 s

³ http://www.iau.org/static/resolutions/IAU2000_French.pdf

⁴ http://www.iau.org/static/resolutions/IAU1991_French.pdf

⁵ http://www.iers.org/nn_11216/SharedDocs/Publikationen/EN/IERS/Publications/tn/TechnNote29/tn29_019,templateId=raw,property=publicationFile.pdf/tn29_019.pdf

⁶ http://www.iau.org/static/resolutions/IAU1991_French.pdf

⁷ http://www.iau.org/static/resolutions/IAU2006_Resol3.pdf

⁸ <http://www.bipm.org/en/committees/cc/cctf/ccds-1970.html> (Note the 1980 amendment and the little box on the right indicating the change implicit by the IAU 1991 Resolution A4)

TAI is a special case of the atomic time scales because the only valid realization is the one in Circular T which is published in arrears by the BIPM. As such a FITS keyword value of 'TAI' should only be used for timestamps which have been reduced using a chain of chronometers traceable through Circular T. TAI should not be used casually.

For example, there are GPS devices which provide time stamps that claim to be TAI (e.g., <http://www.meinberg.de/english/products/gps170pci.htm> but I don't want to name such names in the paper). It is inappropriate to designate a time scale such as TAI(GPS). For the sake of precision the FITS keyword for the time scale in this case should be 'GPS' along with a TOFFSET of 19 s because these time stamps cannot be TAI until they are reduced using next month's Circular T value for the offset of UTC(USNO).

A.6. GPS time

GPS time is defined by the document "ICD-GPS-200, Revision C with IRNs 1 through 5". Note that GPS time is defined in terms of UTC(USNO). That is to emphasize that GPS time is *not* defined in terms of TAI. GPS time is only required to match UTC to within a microsecond.

GPS time is practical, but precision timestamps want to know whether the receiver has implemented the corrections to the satellite clocks and ionosphere given by the contents of Subframe 1 as documented in section 20.3.3.3 of the ICD.

(SLA) At this moment I do not have a suggestion for specifying a parenthetical expression to indicate whether or not the satellite clock correction has been applied. In the absence of a parenthetical expression indicating whether the corrections have been applied the precision of an instant expressed in time scale 'GPS' should be 1 microsecond.

A.7. UTC

UTC is defined by ITU-R TF.460, and according to that specification the broadcasters are only required to match to within a millisecond. Because of the international recommendations and treaty obligations regarding its use, most national metrology agencies have adopted UTC and disseminate it as part of their statutory obligation.

UTC from any source is practical, but precision timestamps want to know which realization was used.

UTC from a GPS receiver is also practical, but precision timestamps want to know whether the receiver has implemented the corrections given by the contents of Subframes 4 and 5 as documented in section 20.3.3.5 of the ICD.

(SLA) At this moment I do not have a suggestion for specifying a parenthetical expression to indicate whether or not the polynomial clock correction between GPS time and UTC(USNO) has been applied.

I suppose perhaps that UTC(GPS) might literally mean GPS time with the leap seconds subtracted away, and if the polynomial is applied then it would be UTC(USNO).

In the absence of a parenthetical expression indicating a particular realization the precision of an instant expressed in time scale 'UTC' should be 1 millisecond. We might offer that UTC(TAI) would mean UTC corrected after the fact by using the offset values published in the subsequent Circular T.

UTC with its current definition was not available prior to 1972. Aside from historical tabulations, most terrestrial time stamps prior to 1972 should be expressed as UT.

A.8. GMT

(SLA) With regret for Pete's work, I do not believe that there is any useable definition for GMT. I've looked at the recommendations of IAU 1935⁹ and they do not actually contain the ruminations from the proceedings wherein the various commissions basically capitulate that GMT can continue to be used so long as it is reckoned from midnight.

(SLA) I think we have to disallow GMT and only allow UT. This is consistent with the wording of the FITS Y2K agreement which is now incorporated in the FITS standard v3.0.

(AHR) Proposed text:

Greenwich Mean Time (GMT) is an ill-defined timescale that nevertheless stubbornly continues to persist in popular parlance as well as scientific papers. Its use is to be discouraged, but if encountered it should be interpreted as UTC, with the caveat that it is rather loosely defined as such and any assertions as to the precision of the time stamps should be regarded with caution.

A.9. UT

The underlying concept for UT originated at the International Meridian Conference held in Washington in 1884 which defined the Universal Day as a mean solar day to be reckoned from Greenwich midnight. UT was initially defined by Newcomb's fictitious mean sun Tables of the Sun, Astr. Papers Amer. Ephemeris 6, 1895 The name Universal Time was established as the subdivision of the Universal Day by Commission 4 of the IAU at the IIIth General Assembly in 1928 at Leiden¹⁰.

Most terrestrial time stamps prior to 1972 should be expressed as UT. For events with time stamps established by radio transmissions we note that it is possible to use Bulletin Horaire of the BIH to obtain sub-second precision on one of the time scales here.

⁹ http://www.iau.org/static/resolutions/IAU1935_French.pdf

¹⁰ http://www.iau.org/static/resolutions/IAU1928_French.pdf

In exceptional cases of events with time stamps established by chronometers at observatories with meridian instruments, calibration is possible to sub-second precision as far back as 1830¹¹.

Appendix B: Unresolved Issues

This is not part of the paper. It is merely a list of issues that we still have to attend to or comments that require review.

- I have added Tropical Year and Besselian Year as units and Julian and Besselian Epochs as time instants. It appears in sections 3, 3.6, 4.1, 4.3, 5.3, and Table 8.
- Appendix A has a number of paragraphs (the ones in red) that need to be cleaned up or finalized. Most, if not all, are on Steve's plate.
- Appendices traditionally have not been considered to be part of the standard. I have reversed that for Appendix A (see end of section 2).
- The FITS ISO-8601 standard has been expanded to also allow signed five-digit years.

¹¹ <http://adsabs.harvard.edu/abs/1994GeoJI.117..811J>